PCL AIR TREATMENT/REG./LUB. | (0-12 BAR) | PREM. -1/2 INCH

Our FRL range includes combination units with 1/4" and 1/2" inlet ports. Adding a PCL Air Treatment unit into an air line efficiently filters to 10 microns. Products feature polycarbonate bowls, allowing the user to easily monitor the element's condition and the collected liquid's level. The bowl is surrounded with protective metal as a safety measure to protect the user in case of excessive pressures, temperatures, or aggressive chemicals.

FILTER-REGULATOR & LUBRICATOR

PCL's FRL Units are designed to control output air pressure, eliminate moisture and contaminants from the air flow, and to lubricate tools during use.

Features

- Selectable manual/semi-automatic drain
- Polycarbonate bowl
- Locking device
- 10 micron filter
- Complete with wall bracket and pressure gauge

The har / 230 psi Clean with water only DO NOT USE ALCOHOL	MAX 18 BAR Max Temp. 60° C Max inlet pressure 16 bar / 230 psi Clean with water only DO NOT USE ALCOHOL
PCL	FPCL

ΡΟ

Part Number	Port Size (in)	Adjustment	Max.Inlet Pressure	Flow@6 bar
ATCFRL12	1/2 mm	0-12 bar/170psi	16 bar	5,000 l/min

Showroom	
Tools & Equipment Way No 7721, Road No 5, Mabela Industrial Area, Muscat, Oman.	Head Office
Mabela Showroom: 9396 6865 Sohar - 9133 2946, Salalah - 7193 6778 Nizwa - 7158 3574, Jalan Bani Bu Ali - 9988 2973 9983 3239, 9320 0399, 9897 5620,9381 9668, 9915 9088, 91788 597, 91742 867, 9386 2790 2246 4851 Toll Free: 8000 4321	Opal Marketing & Industry LLC P.O. Box - 273, Ruwi, Postal Code: 112, Muscat, Oman. 2447 8568, 2447 9986 Fax: 2447 8566
🌐 www.opalte.com 🖪 Opal Tools & Equipment - Oman 🛛 🞯 opaltoolsandequipment	www.opalgcc.com