

The GYSFLASH 101.24 CNT FV is a 100 A high power CONNECTED charger with inverter technology. It allows to keep a 6 V, 12 V and 24 V lead or lithium battery (Lithium-ion «standard» + Lithium-iron Phosphate) at a perfectly stabilized voltage during the diagnostic phases. It will deliver the best charging cycle recommended for the maintenance of the most advanced vehicles on the market. Its USB connectivity makes it 100% customizable.

4 OPERATING MODES

- **Charge:** for 6, 12 or 24 V Lead or Lithium batteries from 5 to 1
- **Diagnostic:** supports up to 100 A for 12 V or 24 V batteries in vehicles in the diagnostic phase, in maintenance workshops.
- **Showroom:** provides power compensation when using the electrical accessories of a demonstration vehicle. It also manages the optimal charging of the battery.
- **Tester:** Allows you to check the battery voltage, evaluate the starting system (starter + battery) and the condition of the vehicle's alternator.

100% CONNECTED

- Add, delete or modify charging modes and profiles via USB.
- Import predefined configuration files adapted to the load trades.
- Retrieve the charging history and data on a USB stick and use them on a spreadsheet.
- Connect additional modules (printer, barcode reader, etc.) via its dedicated module socket (SMC: Smart Module Connector).

100% CONNECTED

- Add, delete or modify charging modes and profiles via USB.
- Import predefined configuration files adapted to the load trades.
- Retrieve the charging history and data on a USB stick and use them on a spreadsheet.
- Connect additional modules (printer, barcode reader, etc.) via its dedicated module socket (SMC: Smart Module Connector).

TECHNOLOGIES & ADVANCED FUNCTIONS

- **FV Flexible Voltage**, the charger operates with a supply voltage between 85 and 265 V.
- **«Auto-Detect»** function automatically starts a charge when a battery is connected to the charger.
- **«Auto-Restart»** function in the event of a power failure with memory of the settings.
- **Cable inspection and calibration**
- **Locking**, avoids the risk of improper handling, ideal for garages and exhibition halls.
- Up to **12 charging profiles available**, including the Easy profile for simplified charging suitable for all lead batteries.

SAFETY

- Protection of the vehicle's on-board electronics: protection against short circuits, polarity reversal and overcharging. Spark prevention system.
- Interchangeable fusible which protect against misuse.
- Temperature sensor to prevent internal electronics overheating.

ADVANCED INTUITIVITY

- **Durable case** with shock and vibration absorbing pads.
- **Low height** (13 cm) for the loader to pass under a vehicle.



SMC USB



Intuitive interface available in 22 languages

ACCESSORIES



V	50/60Hz	Icharge	Charge	Zz	Ondulation/Ripple	Charging curve		40°C @100%	25°C @100%	kg	mm	SOS recovery	IP	150 A	2.5 m
6/12 V	100-127 V AC	1500 W	100 A	5 < 1200 Ah	<0.2 Ah/month	<150 mV Rms	IU _o I _u	47 A	72 A	6.5	325 x 130 x 270	Automatic >2V	IP 20	150 A	2.5 m
	220-240 V AC							68 A	89 A						
24 V	100-127 V AC	1500 W	50 A	5 < 1200 Ah	<0.2 Ah/month	<150 mV Rms	IU _o I _u	35 A	50 A	6.5	325 x 130 x 270	Automatic >2V	IP 20	150 A	2.5 m
	220-240 V AC							59 A	76 A						

CE - EN 60335-2-29

MADE in FRANCE

Showroom



Tools & Equipment

Way No 7721, Road No 5, Mabela Industrial Area, Muscat, Oman.

Mabela Showroom: 9396 6865

Sohar - 9133 2946, Salalah - 7193 6778

Nizwa - 7158 3574, Jalan Bani Bu Ali - 9988 2973

9983 3239, 9320 0399, 9897 5620, 9381 9668, 9915 9088, 91788 597, 91742 867, 9386 2790

2246 4851 | Toll Free: 8000 4321

www.opalte.com Opal Tools & Equipment - Oman opaltoolsandequipment

Head Office



Opal Marketing & Industry LLC

P.O. Box - 273, Ruwi, Postal Code: 112, Muscat, Oman.

2447 8568, 2447 9986 | Fax: 2447 8566

www.opalgcc.com